

# STRAIT-FLEX®

*New Concept Drywall Products*

## WIDE-FLEX 400

<b>DESCRIPTION (Speed, Perfection and Longevity)</b>	Patented PVC tight fibered cotton composite corner tape with diamond-punched paper edging that is 4" wide, .025" thick and comes in 100' rolls. Strait-Flex Wide-Flex 4 has PUR-laminated nose to protect against paper fuzz-ups during finishing and sanding.
<b>ADVANTAGES</b>	<ul style="list-style-type: none"> <li>• <b>Hard-to-Straighten Vaults, Butterfly Vaults, Outside Corners and Obtuse Angles.</b></li> <li>• <b>Straightens small framing irregularities.</b></li> <li>• <b>Memory-free hinge design allows for ease of installation and straighter corners.</b></li> <li>• <b>Installs fast using standard compounds. No special tools or fasteners needed. No nail pops.</b></li> <li>• <b>Inside 90° corners where a large fill or straightening is required, or where strength and speed of finish are required.</b></li> <li>• <b>Diamond-punched paper ensures ultimate bonding and faster drying.</b></li> <li>• <b>Second coat of compound can be applied immediately-very light skim coat to finish.</b></li> <li>• <b>Use in place of metal cornerbead.</b></li> <li>• <b>Rustproof.</b></li> <li>• <b>No. Cracks. No Callbacks.</b></li> </ul>
<b>WARRANTY</b>	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
<b>DIRECTIONS</b>	<ul style="list-style-type: none"> <li>• <b>Cut Strait-Flex to desired length. Adjust to desired angle.</b></li> <li>• <b>Apply using a liberal coat of all-purpose compound with joint knife. Use tile setting compounds in wet areas.</b></li> <li>• <b>Press Strait-Flex into wet compound. Adjust if necessary to create straight line and wipe down with joint knife. Immediately apply light skim coat and let dry.</b></li> <li>• <b>Apply final coat, let dry and sand.</b></li> </ul>
<b>STORAGE</b>	Store in dry place protected from moisture.

**Submittal Approvals:**

Job Name:	
Contractor:	Date: